

What I claim is:

1. For use with a laser source providing light along a reference axis, an optical filter comprising:

a first filter element having a first angular sensitivity to the reference axis; and

a second filter element having a second angular sensitivity to the reference axis that opposes the first angular sensitivity to the light.
2. The optical filter of claim 1, wherein the second angular sensitivity substantially cancels the first angular sensitivity.
3. The optical filter of claim 1, wherein the first angular sensitivity is a positive angular sensitivity and wherein the second angular sensitivity is a negative angular sensitivity.
4. The optical filter of claim 1, wherein the first filter element is a first etalon and the second filter element is a second etalon, wherein the first etalon forms a first acute angle with the direction of incidence and wherein the second etalon forms a second acute angle with the direction of incidence.
5. The optical filter of claim 4, wherein the first acute angle is substantially equal to the second acute angle.
6. The optical filter of claim 1, wherein at least one of the first filter element and the second filter element is a tunable filter element.
7. The optical filter of claim 6, wherein the tunable filter element comprises a first resistive element for heating the tunable filter element.
8. The optical filter of claim 7, wherein the tunable filter element comprises a second resistive element for measuring a tunable parameter of the tunable filter element.

9. The optical filter of claim 1, further comprising a detector coupled to measure a tunable characteristic of the light.
10. The optical filter of claim 9, wherein the tunable characteristic is wavelength.
11. The optical filter of claim 1, wherein the first angular sensitivity is offset from the second angular sensitivity.
12. The optical filter of claim 1, further comprising a support disposed between the first filter element and the second filter element.
13. A laser device comprising:
 - a gain medium;
 - a laser cavity for receiving a light from the gain medium; and
 - a filter apparatus disposed to receive the light, the filter apparatus and the laser cavity defining a reference axis, the filter apparatus having a first angular sensitivity to the reference axis and a second angular sensitivity to the reference axis that substantially cancels the first angular sensitivity.
14. The laser device of claim 13, wherein the filter apparatus is disposed within the laser cavity.
15. The laser device of claim 13, wherein the filter apparatus is external to the laser cavity.
16. The laser device of claim 13, wherein the filter apparatus comprises a first etalon forming a first angle with the reference axis and a second etalon forming a second angle with the reference axis that is equal and opposite to the first angle.
17. The laser device of claim 13, wherein the filter apparatus is a temperature tuning apparatus.

18. A transponder comprising:
- a receiver;
 - a transmitter; and
 - a laser source having a filter apparatus disposed to receive a laser energy, where the filter apparatus has a first angular sensitivity to a reference axis of the laser source and a second angular sensitivity to the reference axis that substantially cancels the first angular sensitivity.
19. The transponder of claim 18, wherein the filter apparatus includes a first filter element and a second filter element, wherein the first filter element forms a first angle with the reference axis and wherein the second filter element forms a second angle to the reference axis that is equal and opposite to the first angle.
20. The transponder of claim 18, wherein the filter apparatus is tunable.